

<b>CONSTRUCTION</b>	Tufting 5/64" cut pile	<b>STAIR SUITABILITY</b>	EN 1963
<b>STRUCTURE</b>	Tufté 5/64" velours	<b>ESCALIERS</b>	A: intensive use
<b>STRUKTUR</b>	Getuftet 5/64" Velours	<b>TREPPENEIGNUNG</b>	
<b>STRUCTUUR</b>	Getuft 5/64" velours	<b>TRAPPENGESCHIKTHEID</b>	
<b>PILE MATERIAL</b>	100% PA 6 IMPREL®	<b>PERMANENTLY ANTISTATIC</b>	ISO 6356
<b>COMPOSITION DU VELOURS</b>		<b>ANTISTATIQUE PERMANENT</b>	≤ 2 kV
<b>POLMATERIAL</b>		<b>PERMANENT ANTISTATISCH</b>	
<b>POOLMATERIAAL</b>		<b>PERMANENT ANTISTATISCH</b>	
<b>PRIMARY BACKING</b>	Non woven PES	<b>IMPACT NOISE RATING</b>	ISO 140-8
<b>SUPPORT</b>	Non tissé	<b>ISOLATION PHONIQUE</b>	ca. 24 dB ΔLw (AB)
<b>TRÄGERMATERIAL</b>	Vlies	<b>TRITTSCHALLVERBESSERUNG</b>	ca. 29 dB ΔLw (UX)
<b>TUFTDOEK</b>	Felt	<b>GELUIDSISOLATIE</b>	
<b>SECONDARY BACKING</b>	Action back	<b>SOUND ABSORPTION</b>	ISO 354
<b>DOSSIER</b>	Ultratex® back	<b>ABSORPTION PHONIQUE</b>	0.20 αw (AB)
<b>RÜCKEN</b>		<b>SCHALLABSORPTIONSGRAD</b>	0.30 αw (UX)
<b>TAPIJTRUG</b>		<b>GELUIDSABSORPTIE</b>	
<b>PILE WEIGHT</b>	Ca. 630 gr/m <sup>2</sup>	<b>THERMAL RESISTANCE</b>	ISO 8302
<b>POIDS DU VELOURS</b>		<b>RÉSISTANCE THERMIQUE</b>	0.07 m <sup>2</sup> K/W (AB)
<b>POLEINSATZGEWICHT</b>		<b>WÄRMEDURCHLASSWIDERSTAND</b>	0.13 m <sup>2</sup> K/W (UX)
<b>POOLGEWICHT</b>		<b>WARMTEDOORLAATWEERSTAND</b>	
<b>TOTAL WEIGHT</b>	Ca. 1.600 gr/m <sup>2</sup>	<b>FASTNESS TO LIGHT</b>	ISO 105-B02
<b>POIDS TOTAL</b>		<b>SOLIDITÉ A LA LUMIÈRE</b>	≥ 5-6
<b>GESAMTGEWICHT</b>		<b>LICHTECHTHEIT</b>	
<b>TOTAAL GEWICHT</b>		<b>LICHTECHTHEID</b>	
<b>PILE HEIGHT</b>	Ca. 4,1 mm	<b>COLOUR FASTNESS TO WATER</b>	EN ISO 105-E01
<b>EPAISSEUR DU VELOURS</b>		<b>SOLIDITÉ À L'EAU</b>	≥ 4-5
<b>POLHÖHE</b>		<b>WASSERRECHTHEIT</b>	
<b>POOLHOOGTE</b>		<b>WATERECHTHEID</b>	
<b>TOTAL HEIGHT</b>	Ca. 6,5 mm	<b>FIRE RESISTANCE</b>	EN 13501-1
<b>EPAISSEUR TOTALE</b>		<b>COMPORTEMENT AU FEU</b>	Bfl-s1 if glued (AB)
<b>GESAMTHÖHE</b>		<b>BRENNVERHALTEN</b>	Cfl-s1 (UX)
<b>TOTALE DIKTE</b>		<b>BRANDGEDRAG</b>	
<b>TUFT DENSITY</b>	Ca. 378 000/m <sup>2</sup>	<b>RUBBING FASTNESS</b>	EN ISO 105-X12
<b>NOMBRES DE POINTS</b>		<b>SOLIDITÉ AU FROTTEMENT</b>	≥ 4
<b>NOPPENZAHL</b>		<b>REIBECHTHEIT</b>	
<b>AANTAL PUNTEN</b>		<b>WRIJFECHTHEID</b>	
<b>PILE DENSITY</b>	Ca. 0.107 g/cm <sup>3</sup>	<b>NUMBER OF COLOURS</b>	7
<b>DENSITÉ DU VELOURS</b>		<b>NOMBRES DE COULEURS</b>	
<b>POLROHDICHTHEIT</b>		<b>ANZAHL FARBEN</b>	
<b>POOLDICHTHEID</b>		<b>AANTAL KLEUREN</b>	
<b>CLASSIFICATION</b>	EN 1307	<b>WIDTH</b>	EN ISO 3018
<b>CLASSEMENT</b>	32 - LC2	<b>LARGEUR</b>	ca. 400 cm
<b>KLASSIFIKATION</b>		<b>BREITE</b>	
<b>CLASSIFICATIE</b>		<b>BREEDTE</b>	
<b>UPEC</b>	U3 P3 E1 C0 (AB)		
<b>CHAMBORD AB</b>	Certification CSTB: 10/265 (AB)		
<b>CASTOR CHAIR SUITABILITY</b>	EN 985		
<b>CHAISE À ROULETTES</b>	A: intensive use		
<b>STUHLROLLENEIGNUNG</b>			
<b>ROLSTOELGESCHIKTHEID</b>			



AB / UX



AB

UX

EN14041



16

ITC CO BV

Kanegemstraat 15 - BE 8700 Tielt

DOP: 1011#IE0ABV

Textile Floor Covering EN1307

Notified body 2401



my.itc-carpets.com

AB

REG. NR  
**A05F03BE**  
www.pro-dis.info



20

ITC CO BV

Kanegemstraat 15 - BE 8700 Tielt

DOP: 1011#IE0ACL

Textile Floor Covering EN1307

Notified body 2401



my.itc-carpets.com

UX

REG. NR  
**48FC1709**  
www.pro-dis.info



AB / UX



moquettes touffetées et tissées en lés  
<http://evaluation.cstb.fr>

AB